

MB 8020 DOT PIN MARKER



The World's Most Compact

MB 8020

Versatile Part-Marking Solution

The mid-sized MB 8020 marker has a marking area of 3.15 inch (80mm) by 0.78 inch (20mm) that give high quality marks including serial numbers, logos, date/time stamps, Data Matrix or QR Codes. Versatile and functional, MB 8020 is well-suited for use in aerospace, automotive, mechanical, oil, gas and many more applications. The brain of the MarkinBOX pin markers is the MB2 controller, incorporating input from sketchbook software.

Key Features



Here is MB 8020 with Windows PC* and MB2 controller

- * other option: Android devices
- Fully Electric



Runs safely and efficiently with maximum uptime and little maintenance

Equiped with dustproof shutter



Small, Easy to UseLightweight and portable, it fits in the palm of your hand

Windows Based Software sketchbook software is able to run with Windows XP, 7 and 8

- Wide Choice of Connectivity 6 possible ways to start marking via USB, Bluetooth (PC or Android), Digital I/O, PLC or Ethernet communications
- High Quality Mark Guaranteed high quality marks just over 3 inches (80mm)
- Flexible Integration
 Can be hand held, mounted or integrated into production

Available Accessories




parts with a range of diameters

(3"or 5")



Stand Mount





Marking Samples

















The World's Most Compact

Connectivity

USB Communication



Android Communication




PLC Communication




Bluetooth Communication



D.I/O Communication



Network Communication



sketchbook Software

The sketchbook software is intuitive for every user, with WYSIWYG drag and drop features, built-in logo software, CSV file marking, DXF file conversion, error log and many other features.









Color options



SPECIFICATIONS - MB 8020





Marking Head, Marking Stand

Marking Area	X axis 3.1" (80mm) Y axis 0.8" (20mm)
Marking Head Dimensions	6.6" (W) x 3.1" (D) x 8.4" (H) (168mm x 79.5mm x 213mm)
Marking Head Weight	4.6lbs (2.1Kg)
Marking Head Cable	10' (3m) cable option : 16' (5m) cable
Marking Stand Weight	15.4lbs (7Kg)
Marking Technology	Solenoid Drive


MB2 Controller

Controller Power	AC 100v – 240v 50/60Hz
Controller Dimensions	2.6"(W) x 5.7"(D) x 8.7"(H) (66mm x 144mm x 220mm)
Controller Weight	3.1lbs (1.4kg)
Approvals	UL & CE on adaptor
Communication Ports	USB / RS232 / LAN / Bluetooth / DIO
I.O.	Input 12 / Output 8 point
Message Memory	255 message storage on controller

sketchbook Software

OS	Windows XP/7/8
Memory / Display	1 GB / 1280 x 768 dpi
Character Height	.04" ~ .08" (1~20mm) (0.1mm Pitch)
Character Width	Height x 10% ~ 200%
Character Pitch	.04" (0.1mm Pitch)
Character Fonts	TOCHO, Elegant, 5 x 7, PC Font when linked to PC
Logos	JPEG, BMP, DXF, logo generator
Serialization	00000001 – 99999999, 4 serial numbers
2D Codes	Data Matrix & QR Code
Date & Time	Julian date

Blueprint - MB 8020











































403 S. Hawley Rd. Milwaukee,WI 53214 (800)-837-9270

